

Product data sheet

6004 CT-12

EAN-No. 4000896260041



Length: 196 mm · Torque range min-max: 0.2 – 1.2 Nm · Accuracy: 6 % ·



- "Ratchet function" with free-running mechanism, featuring right · left · fixed switching · enables fast work thanks to smooth re-gripping when operating screw connections, even in confined installation spaces
- Excellent readability of the torque setting thanks to large, clear numerical display
- Short 36° release distance with ergonomic release behaviour and clearly audible signal
- Bit holder with quick-release fastener – fast bit change with one hand
- Release mechanism made of high-alloy tool steel with excellent wear resistance
- Exceeding the set torque is prevented by the overload clutch ("slipper")
- Easily recognisable locking status by means of lock symbols
- With calibration certificate and serial number
- Calibration and repair capability at the HAZET Service Centre in Remscheid
- Ergonomically shaped HAZET 2-component handle
- Tested in accordance with DIN EN ISO 6789-2:2017
- Made in Germany
- Output:
- Dimensions: 196 mm
- For manual operation
- Torque range min-max: 0.2 – 1.2 Nm
- Accuracy: 6 %
- Scale Graduation (Nm): 0.01 Nm

Handle	Ergonomically shaped HAZET 2-component handle
Order Number	6004 CT-12